

# ESONE®

PTFE & Silicone Coated Fiberglass Fabric & Belt

## TDS of INDUSTRIAL SERIES YS7011AJ

Product	Product Category	Coating
PTFE GLASS FABRIC SELF ADHESIVE	INDUSTRIAL SERIES	SILICONE PRESSURE SENSITIVE ADHESIVE

Properties	Metric	Imperial
Standard width Please ask for other widths	1000, 1250 mm	39.5, 49.3 inches
Backing thickness PTFE Glass	0.11 mm	0.0043 inches
Total Thickness PTFE Glass and Silicone PSA	0.16 mm	0.0063 inches
Baking weight PTFE Glass	220 g/m <sup>2</sup>	6.5 oz/yd <sup>2</sup>
Tensile Strength	240 N/cm      Warp	137 lbs/inches      Warp
	200 N/cm      Fill	114 lbs/inches      Fill
Adhesion	5.4 N/cm	49 oz/inches
Temperature resistance	-73 to +260 °C	-100 to +500 °F

ESONE® Industrial Series PTFE coated fiberglass fabric with Silicone pressure sensitive adhesive, has easy release surface and can continuous working from -73 to +260 °C. With back side yellow textured PVC release liner for ease of application.

It's widely used in applications such as release adhesive tape for form fill, impulse/L-bar, polybag sealing and heat press machines, covering drying cylinders, wire and cable insulation and protection for LCD/FPC/PCB industry, non stick roll coverings for printing and textile, PVC window laminating, composit mold release and bonding.



ESONE® is a registered trademark owned by  
 Jiangsu Eson New Material Co.,Ltd  
 Taixing Youngsun FL-Plastics Co.,Ltd  
 Western End of South Third Ring Road, Taixing, Jiangsu, China  
 Tel: 0523-8759020      E-Mail: sales@chinayoungsun.com

[www.ptfe-fabrics.com](http://www.ptfe-fabrics.com)