


ESONE®

PTFE & Silicone Coated Fiberglass Fabric & Belt

TDS of STRONGER FIBERGLASS SERIE YS6008S-S



Product	Product Category	Coating
PTFE GLASS FABRIC	STRONGER FIBERGLASS SERIE	PTFE

Properties	Metric	Imperial
Standard width Please ask for other widths	1000, 1350, 2700 mm	39.5, 53, 106 inches
Mesh Size	4x4 mm	4x4 mm
Weight	1180 g/m ²	34.8 oz/yd ²
Fiberglass	Stronger Fiberglass	Stronger Fiberglass
Tensile Strength	480 N/cm Warp	274 lbs/inches Warp
	940 N/cm Fill	537 lbs/inches Fill
Color	Brown	Brown
Temperature resistance	-73 to +260 °C	-100 to +500 °F

ESONE® stronger fiberglass series is using stronger fiberglass yarn for weaving, the tensile strength and lifetime of YS6008S-S is much better than standard mesh series.

The main applications is screen printing, drying, packaging industry, textile industry, wood processing industry and so on, which is used as heat resistant and non stick conveyor belt to transport materials through ovens.

4x4 mm PTFE open mesh fabric is FDA & LFGB certificated, can be used in direct contact with food.



ESONE® is a registered trademark owned by
 Jiangsu Esoner New Material Co.,Ltd
 Taixing Youngsun FL-Plastics Co.,Ltd
 Western End of South Third Ring Road, Taixing, Jiangsu, China
 Tel: 0523-87590206 E-Mail: sales@chinayoungsun.com